

Product Name :
Biological Safety Cabinet moveable with Castors India

Product Code :
NG826



Description :

Biological Safety Cabinet moveable with Castors India

Technical Specification :

Standard Features

- Motorized front Window
- Large LCD display
- Automatic Airspeed adjustable with filter block
- Side & back wall is made up of single piece stainless steel
- Interlock function: Fluorescent lamp and front window; Fluorescent lamp and blower, UV lamp; Blower and front window
- Front 10°slanted to offer operator comfort while working for long time, reduce glare and maximize reach into the work area.

Description:

- External Dimensions (Width x Depth x Height): Min. 1,420 x 852 x 1,540 mm or equivalent
- Internal Work Area (Width x Depth x Height): Min. 1,270 x 623 x 670 mm or equivalent
- Usable Work Area: Min. 0,6 m²
- Tested Opening: Min. 220 mm
- Working Opening: Min. 270 mm
- ULPA Filter Efficiency: > 99.999%
- Fluorescent Lamp Intensity: Min. 1400Lux

- Cabinet Construction:
 - Main body: 1.5mm 18-gauge electro-galvanized Steel with oven-baked epoxy- polyester Isocide antimicrobial powder-coated finish or equivalent
 - Work Zone and Side wall s: 1.5 mm 16-gauge stainless steel 304 304, with 4B finish or equivalent
 - Power supply: 220-240V, 50Hz, 285W ± 10%
 - Net Weight: 280 kg ±5%
 - Gross Weight (Without Base Stand): 345 kg ±5%
 - Must include accessories:
 - UV Lamp for 4ft, 5ft, 6ft Cabinets except AC3-4B
 - Direct Mounted Electrical Outlet- Plug Code C
 - Support Stand with Caster Wheels (Height 28. ') for 4ft cabinets
 - Vertical Laminar Flow Cabinet
 - Glass Sides (4ft/ 1.2m W, 2ft/0.6m H)
 - Manual guidebook: English language

Naugra Export

Website: www.naugraexport.com, **Email:** sales@naugraexport.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, **Phone:** +91-0171-2643080, 2601773