Phone: +91-0171-2643080, 2601773
Email : sales@naugraexport.com

Product Name :	**Product Code :**
DIGITAL WATTMETER (THREE PHASE)	Physics Lab0002

Description :

DIGITAL WATTMETER (THREE PHASE)

We are Leading Supplier of DIGITAL WATTMETER (THREE PHASE) in India. We also bulk supply DIGITAL WATTMETER (THREE PHASE) for laboratory tensers.

Digital Wattmeter (Three Phase)
Technical Specifications

3 Phase Meter with Power Analyzer
Built in Clock, calendar and real time data logger with SD memory card
Measurement : ACA, ACV, Active/True Power, Apparent power, Reactive Power, Power Factor, Phase Angle, frequency
display : 3.2” x 2.4” LCD and 320 x 240 pixel dot matrix LCD with backlight
Wire connectors : 1P/2W, 1P/3W, 3P/3W, 3P/4W
Safety standard : IEC 1010 CAT III 600V
ACV input impedance : 10Mâ„¦
Clamp frequency response : 40Hz ~ 1KHz
Tested frequency : 45Hz ~ 65Hz
Sampling time : Approx. 1 sec.
Computer Interface : USB / RS 232

Electrical Features :

ACV range : 10V ~ 600V
Resolution : 0.1V, Accuracy : ±(0.5% + 0.5V)
ACA range : 20A ~ 1200A
Resolution : 0.001A ~ 1A; Accuracy : ±(0.5% + 5A)
Power factor range : 0.00 ~ 1.00
Resolution : 0.01; Accuracy : ±0.04
Phase angle range : -180º ~ 180º
Resolution : 0.1º, Accuracy : ±1º
Frequency range : 45 ~ 65Hz
Resolution : 0.1Hz, Accuracy : 0.1Hz
Active power range : 0.000 ~ 9.999 MW
Apparent power range : 0.000 ~ 9.999MVA
Reactive power range : 0.000 ~ 9.999MVAR
Active power hour range : 0.000 ~ 9.999MWH
Apparent power hour range : 0.000 ~ 9.999MVAH
Reactive power hour range : 0.000 ~ 9.999MVARH

Naugra Export

Website: www.naugraexport.com, **Email:** sales@naugraexport.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, **Phone:** +91-0171-2643080, 2601773