

<b>Product Name :</b> Direct Shear (Motorised Twelve Speed) For Testing Lab for Soil Testing Lab	<b>Product Code :</b> NSOL-T52
---	-----------------------------------



**Description :**

for Soil Testing - The apparatus comprises of the following.

**LOADING UNIT :**

Supplied with load yoke with direct and lever system for applying load. Normal stress capacity 8 kg/sq. cm. Load is applied either directly or through a counter balanced detachable lever. Provision is made for the load to be applied either through a steel ball recessed in the loading pad or direct through a boss on the pre calibrated loading yoke. The loading unit is provided with V strips and roller strips for frictionless movement of shear box housing.

**SHEAR BOX ASSEMBLY :**

Comprising direct shear box in two halves for a square specimen size 60 x 60 x 25mm one pair of plain gripper plates, One pair of perforated gripper plates, one pair of porous stones, one top of loading pad.

**SHEAR BOX HOUSING:**

Accommodates the direct shear box assembly. Complete with two ball roller strips. Specimen cutter : for cutting 60 x 60 x 25mm. Specimen form larger samples. Set of weights to give a normal stress of 3kg/sa.cm. Through larger as following : -

To give kg/cm. 0.05,Qty. 4 nos.

To give kg/cm. 0.1,Qty. 1 no.

To give kg/cm. 0.2,Qty. 1 no.

To give kg/cm. 0.5,Qty. 3 nos.

To give kg/cm. 1.0,Qty. 1 no.

Complete set as above but without proving ring. Net weight 140 kg.

**ESSENTIAL ACCESSORIES :**

High sensitivity compression proving ring. Cap 200kg. One consolidation dial gauge 0.01mm x 25mm and one

strain dial gauge 0.01mm x 25mm

OPTIONAL EXTRAS :

2 Additional set of weights to give a normal stress of 5 kg/cm . Soil sampler for 60mm x 60mm specimen and test forms pad of 50.

SPARES : Porous stone for 60mm x 60mm size sample available in pairs. Unit is electrically operated to give the following 12 rates or strains. 1.25, 0.625, 0.25, 0.125, 0.05, 0.025, 0.01, 0.005, 0.002, 0.001, 0.004 and 0.0002 mm/min. The apparatus is suitable for operation on 230 Volts Single Phase A.C. Supply.

[Click here to download PDF.](#)

Direct Shear (Motorised Twelve Speed)

Direct Shear (Electronic 12 Speed Motorised) :

ZI 3051

IS 2720 (PART XIII)

The unit is same as ZI 3051 except that the transducers (i.e. Displacement sensors & S type Load Cell ) with microprocessor display system provided instead of mechanical dial gauges & proving ring. The equipment is supplied with standard accessories for 60 mm shear box. 2 Set of weights to a normal stress of 3 kg/cm on a specimen through a lever is provided in the standard accessories. Additional weights can be ordered at an extra cost

## Naugra Export

**Website:** www.naugraexport.com, **Email:** sales@naugraexport.com

**Address:** 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, **Phone:** +91-0171-2643080, 2601773