

Description :

Seed Germinator - With Refrigeration System. Double walled, inside chamber stainless steel, outer body made of CRC/G.I. powder coated, Temp. Range from 10°C to 60°C controlled by Dual display microprocessor based Digital temp. indicator cum controller with \pm 1°C accuracy or better. Cooling system consist of high efficiency Kirloskar Make compressor with relevant accessories. Humidity range from atmospheric humidity to 95% controlled by Dual display Microprocessor based Digital Temp. Controller (Dry and Wet bulb method) with accuracy + 3% RH or better. Inner water tank made of stainless steel with ball cock valve. Front door has a full view glass observation window.

OPTIONAL FITTING:

Dual display digital temp. controller (For Both Wet & Dry) with printer interface facility (Centronic port) to print set value, actual values, date and time with variable print time interval (Without Printer) at extra cost Microprocessor based direct RH digital controller.

Circular chart recorder - Daily / Weekly type.

Fluorescent tube light provided with 24 hours ON/OFF Programmable timer for Day /Night effect.

Temp.range15° to 60°C.at extra cost.

Automatic Voltage Stabilizer.

Naugra Export

Website: www.naugraexport.com, Email: sales@naugraexport.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, Phone: +91-0171-2643080, 2601773