


Product Name : Triaxial Shear Apparatus (Motorised) Single Speed For Testing Lab for Soil Testing Lab	Product Code : P64
---	------------------------------



Description :

for Soil Testing - For determining the triaxial shear strength of soil specimens of 38mm, 50mm, 75mm and 100mm dia.

CONSISTS OF :

One load frame 5000 Kgf motorised , consists one rate of strain type, giving the following rates of strain. 1.25mm/min . Load frame is supplied with a dial gauge bracket. Universal triaxial cell (stationary bushing) 10kg/cm.sq. One lateral pressure assembly 0-10 kg/cm.sq. One lateral pressure assembly 0-10kg/cm.sq. complete with foot pump and rubber hose. One high sensitivity proving ring capacity 1000kg. One strain dial gauge 0.01 x 25mm. Suitable for operation on 230 V A.C.

[Click here to download PDF.](#)

Triaxial Shear Apparatus (Motorised) Single Speed
Triaxial Shear Test Apparatus (Motorised) 30 Speed : ZI 3062
Same as ZI 3061 but the motorised load frame capacity 5000 Kgf has 30 rates of strain from 0.00048 mm/min to 6.0mm/min . Suitable for operation on 230 V A.C.

ACCESSORIES :

High sensitivity proving ring capacity 2500 Kgs with calibration chart and carrying case.

Naugra Export

Website: www.naugraexport.com, **Email:** sales@naugraexport.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, **Phone:** +91-0171-2643080, 2601773